

FreeSpace® DS 100F Flush-Mount Loudspeakers



Bose® performance,
clean styling and value
for business music systems.



The FreeSpace® DS 100F loudspeakers deliver high-energy, full-range sound, making them well-suited for foreground music applications in retail, restaurant, hospitality and other applications where music and entertainment are key parts of creating a customer experience. These 100-watt loudspeakers can be easily flush-mounted in ceilings up to 30ft (10m) high. Use fewer loudspeakers to create even coverage due to the high output and even dispersion. Deliver pages and announcements with clarity. The DS 100F loudspeakers meet numerous standards for combination music and evacuation systems around the world.

Designed for business music applications.

- > Create energized foreground music environments with exceptional presence, full bass and clear detail.
 - > Clean, sleek styling visually blends into ceilings.
 - > Quickly and easily set taps with a simple turn of an innovative thumb wheel, accessible under the grille.
 - > Versatile for 8Ω or high-impedance use with a built-in multi-tap transformer.
 - > Provides tap settings for 12.5W, 25W, 50W, 100W for 70V use; and 25W, 50W, 100W for 100V use.
 - > Flush or pendant-mount in ceilings up to 30ft (10m).
 - > Acoustically compatible with FreeSpace DS 100SE surface-mount loudspeakers and can be combined on the same loudspeaker line.
- > Each model is available in black or white and can be painted.
 - > Performance can be maximized by using the recommended loudspeaker equalization resident in select Bose® electronics. The loudspeakers can be used out of the box with a 55-Hz high-pass filter when recommended loudspeaker equalization is not used.
 - > Engineered and tested for demanding business environments and backed by a five-year transferable limited warranty.

Bose Professional Systems Division

Design | Performance | Support

BOSE®

Specifications

Driver complement:

One 2.25" (57mm) Twiddler® driver
One 5.25" (133mm) woofer

Maximum acoustic output (pink noise):

105 dB-SPL @ 1m
111 dB-SPL (peak) @ 1m

Impedance:

8Ω (transformer bypass)

Long-term power handling:

100W

Sensitivity (pink noise):

85 dB-SPL, 1W @ 1m

Frequency range (-3 dB):

65 Hz to 16 kHz

Beamwidth (-6 dB point, average 1 – 4 kHz):

160° conical

Construction features:

Enclosure: Injection-molded polypropylene
Grille: Powder-coated steel
Baffle: Injection-molded polypropylene

Finish:

Textured black or white finish with a contoured, powder-coated steel grille. Both the enclosure and grille can be painted.

Connectors:

Three-terminal barrier strip with pre-wired ceramic connector

Color:

Black or white, paintable

Dimensions:

Outer flange diameter: 11.8" (299mm)
Ceiling hole diameter: 10.5" (267mm)
Height to top of housing: 7.6" (193mm)

Weight:

Product: 13lb (5.9kg)
Shipping: 16lb (7.3kg)

For more information:

pro.bose.com

BOSE®
Better sound through research®

All information subject to change without notice.
©2007 Bose Corporation.
Bose and FreeSpace are registered trademarks of Bose Corporation.
CCM-004099 PC042801